

KELLY BUSHINGS

KELLY WIPERS

Kelly Size [inches]	HDP, HDS Square P/N	Weight [lbs/kg]	Hex P/N	Wt [lbs/kg]
3" API	8-0260	4 / 1.8	8-0320	4 / 1.8
3.1/2" API	8-0265	4 / 1.8	8-0285	4 / 1.8
4.1/4" API	8-0170	3.5 / 1.6	8-0275	3.5 / 1.6
5.1/2" API	8-0300	3 / 1.4	8-0305	3 / 1.4
6" API	8-0200	3 / 1.4	8-0240	3 / 1.4

KELLY BUSHING SAFETY GUARD

Fits Rotary Tables with HDP-HDS Kelly Bushings.

For 17.1/2" - 27.1/2" Rotary Table P/N 15794

For 37.1/2" Rotary Table P/N 16951

For 49.1/2" Rotary Table P/N 16953

MPCH MASTER BUSHING

The 37.1/2" MPCH is a Pin Drive Hinged Master Bushing specially designed for floating and semi-submersible drilling operations.

With insert bowl No. 3 and optional insert bowls No. 1 and No. 2, the MPCH will handle 2.3/8" to 13.3/8" OD drill collars, tubing and casing.

Unit come complete with No. 3 insert bowl, bit breaker adapter plate and lifting sling PN 6699.

Part	P/N	Weight [lbs/kg]
Complete	*	4200 / 1905
Body only	*	3200 / 1452
Insert Bowl No. 1: 13.3/8" to 11.3/4"	6610	336 / 152
Insert Bowl No. 2: 10.3/4" to 9.5/8"	6609	470 / 213
Insert Bowl No. 3: API 8.5/8" and smaller	6608	625 / 283
Lifting sling for insert bowls	1021	46 / 22

* See selection chart

MSPC MASTER BUSHING

The 27.1/2" MSPC is a solid Body Pin Drive Master Bushing designed for all drilling operations.

The pin drive allows the Kelly bushing to ride on top of the rotary table and permits extended bowls to be used for better slip back up. With the extended API insert bowl No. 3, the MSPC will handle 2.3/8" thru 8.5/8" OD drill pipe, drill collars, tubing and casing. Insert bowl No. 2 can handle tubulars from 9.5/8" to 10.3/4" OD; while insert bowl No. 1 is good for 11.3/4" to 13.3/8" OD. Unit comes with No. 3 insert bowl, bit breaker adapter plate and lifting sling PN 6699.

Part	P/N	Weight [lbs/kg]
27.1/2" complete	*	1965 / 891
body only	*	1110 / 503
Insert Bowl No.1: 13.3/8" and 11.3/4"	1903	326 / 148
Insert Bowl No.2: 10.3/4" and 9.5/8"	1904	460 / 209
Insert Bowl No.3: API 8.5/8" and smaller	1810	620 / 281
Lifting sling for insert bowls	1021	46 / 22

* See selection chart

MSP MASTER BUSHINGS

MSP 27.1/2" SPLIT PIN DRIVE BUSHINGS*

MSP 27.1/2" Split Pin Drive bushings are also available. With the larger rotary opening the standard No. 3 Extended API taper is used. This allows the use of extra-long SDXL slips required for heavier loads. Weight 1600 lbs / 726 kg.

* See selection chart



MPCH with # 3 bowl and SDXL slips



MPCH with bit breaker adapter plate



MSPC



MSP